Modified Rail - Nap Size Approx. 42"X48"

Fabric in the kit (WOF=width of fabric)

4-61/2" WOF strips

Focus fabric 1/3yard 3/3

4-2 1/2 " WOF strips each of 3 different fabrics

Rails A, B, C 1 vard each

4-3 1/2" WOF strips

Border 3/8 yard

Binding 1/3 yard

5 - 2 1/2 " WOF strips

Backing and batting in kit. One each 45X54 inches

Directions: RST Right sides together

- 1. To make rails: RST, stitch rails (A,B,C) together along length of fabric. Press seams in one direction. Crosscut unit into 9 1/2" segments. Yielding 4 segments each. Repeat this step for the remaining rails You will need fourteen 6½"x½"blocks.
- Crosscut the focus fabric strips into fourteen 9 ½" segments.
- 3. RST, stitch the two blocks together, alternating blocks, 4 blocks to a row.
- 4. RST, stitch rows together. Layout of quilt is 4 blocks across, 7 rows down.
- 5. To add borders: RST, add 3 1/2" border to sides of quilt. Trim excess. Repeat for top and bottom borders. Press borders away from center.
- 6. Place backing right sides down on flat surface. Place batting onto backing.

7. Center quilt top, right side up, onto backing/batting. Baste in place and quilt as Desired.

8 Square up quilt and add binding.



